

DANGER
EXTREMELY FLAMMABLE
VAPORS MAY CAUSE FLASH FIRE

VAPORS MAY IGNITE EXPLOSIVELY, PREVENT BUILDING OF VAPORS --- OPEN ALL WINDOWS AND DOORS. USE ONLY WITH CROSS VENTILATION. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. DO NOT SMOKE. EXTINGUISH ALL FLAMES AND PILOT LIGHTS, TURN OFF STOVES, HEATERS, ELECTRIC MOTORS AND OTHER SOURCES OF IGNITION DURING USE AND UNTIL ALL VAPORS ARE GONE. CLOSE CONTAINERS AFTER USE.

KEEP OUT OF REACH OF CHILDREN

USES

IN THE KITCHEN: To apply sink or counter tops of linoleum, masonite, plastic or wood.

IN THE WORKSHOP: For bonding laminates, tables, chairs, or counters.

IN THE HOME: To mend, leather to leather, rubber to rubber, repairing shoes, mending or replacing wall tile, floor tile or other uses where a grease proof, flexible adhesive is desirable.

IN THE GARAGE: To mend, repair or replace gaskets on car doors, trunks, or windows. (Wipe gaskets and surface clean) with solvent – apply to both surfaces – let dry 15 minutes – press firmly together.

Armor Adhesive is contact cement. Be sure to align piece accurately before bringing together. Also used for bonding dissimilar materials, such as leather, linoleum and thin gauge metals, except copper.

ARMOR ADHESIVE is made from top quality materials – very flexible with many applications.

CAUTION: Store above 50°F – **ARMOR ADHESIVE** has excellent shelf life when stored properly – unopened.

Covers approximately 25 square feet per quart.

Manufacturer makes no warranty of any kind, expressed or implied, concerning the use of this product.

User assumes all risk of use or handling, whether in accordance with directions or not.

Batch No.: _____

Packed by: _____

- 1 U.S. QUART (0.946 Liter)
- 1 U.S. GALLON (3.8 Liter)
- 4 U.S. GALLON (5.15 Liter)

N F P A	HAZARD RATING	Fire
	4-EXTREME	3
	3-HIGH	2
	2-MODERATE	0
	1-SLIGHT	0
0-INSIGNIFICANT	0	Special
	Toxicity	Reactivity



ARMOR ADHESIVE

AD-1303

FOR BONDING

ALL TYPES OF DECORATIVE LAMINATES, CHIPBOARD, WOOD, METAL, HARDBOARD, PLASTIC, PLYWOOD PANELS, LEATHER, RUBBER, CANVAS AND OTHER MATERIALS.

ARMOR ADHESIVE IS FAST DRYING AND RETAINS ITS OPEN TIME LONGER, MAKING IT WELL SUITED FOR THE HOME OWNER OR THE LAYMAN. REQUIRES NO PRESSES OR CLAMPS.

Fast drying, Water Resistant, Permanent – Bonds with simple contact pressure without heat, Clamps or presses.

UN1133

DANGER!

EXTREMELY FLAMMABLE, HARMFUL OR FATAL IF SWALLOWED. DO NOT INDUCE VOMITING. SEE INSTRUCTIONS ON SIDE PANELS.

KEEP OUT OF REACH OF CHILDREN

Manufacturer under contract for



AMERICAN FLOOR PRODUCTS COMPANY, INC.

P.O. Box 7055
Gaithersburg, MD 20898-7055
Phone (800) 342-0424

DANGER
HARMFUL OR FATAL IF SWALLOWED.
IF SWALLOWED DO NOT INDUCE VOMITING.
CALL A PHYSICIAN IMMEDIATELY.
VAPORS HARMFUL.

DIRECTIONS FOR USE:

CAUTION: EXTREMELY FLAMMABLE MIXTURE.

DO NOT USE NEAR HEAT OR FLAME.

USE ONLY IN WELL VENTILATED AREA.

Hazardous ingredients: Methyl Ethyl Ketone, Toluene, Petroleum Distillate.

CAUTION: THIS PRODUCT CONTAINS TOLUENE AS A SOLVENT. TOLUENE IS SUSPECT TO BE A CARCINOGEN AS PER LAB TEST ON RATS.

1. Surfaces to be bonded must be dry and clean.
2. Apply an even coat to both surfaces using brush.
3. Both coated surfaces must be allowed to dry before bonding. This will normally take from 10 to 20 minutes under average conditions. When tacky, the adhesive will adhere but not transfer as a wet film to smooth bag type Kraft paper if touched lightly. If the cement becomes too dry (over 6 hours), it may be reactivated by applying another coat of cement.
4. Bring both surfaces into contact in exact position desired. **ARMOR ADHESIVE** bonds instantly on contact and work cannot be shifted into place.
5. Using roller or rubber mallet, apply pressure over the entire area to insure positive contact. Working from center toward edges in applying pressure can prevent trapping air.
6. **ARMOR ADHESIVE** grows stronger with age. Do not expose assemblies to high heat for at least three days after bonding.
7. **ARMOR ADHESIVE** may be cleaned off tools with solvent.

CAUTION: Extreme care must be used when handling surfaces as bonding is immediate upon contact.

CONTAINER DISPOSAL: WHEN CONTAINER IS EMPTY, PUNCTURE A NUMBER OF TIMES AND CRUSH BEFORE DISPOSAL.

DANGER

Extremely Flammable. Harmful or fatal if swallowed – do not induce vomiting. Keep away from heat, sparks and open flame. Turn off all sources of ignition in the area (electric motors, all appliances, fans, clocks, refrigerators, gas pilot lights, etc.) Do not smoke while using. Use with adequate ventilation. Avoid breathing vapor. Avoid prolonged or repeated contact with skin. Keep container tightly closed when not in use. KEEP OUT OF REACH OF CHILDREN.