

Beholder 3.0 Plugin Guide

Plist Key	Type	Description
Title	String	The name that appears in the Beholder plugins menu (required).
Query	String	A URL that accepts a query parameter (required). %@ must be used to specify the part of the URL that is to be replaced with the user's query.
Separator	String	A string that should be substituted in place of white space in a user's query. If missing, a plus sign (+) is used as the default.
More	String	A URL fragment added to the Query to produce a specific page of results. %d must be used to specify the part of the URL that is to be replaced with the page number.
MoreQuery	String	A URL used in place of the Query to produce a specific page of results (use instead of More). %@ must be used to specify the part of the URL that is to be replaced with the user's query. %d must be used to specify the part of the URL that is to be replaced with the page number. %@ must precede %d.
MoreStart	Number	A value used to compute a page of results (page number to replace %d = MoreStart + (MoreOffset x page)). If missing, the value 0 is used as the default.
MoreOffset	Number	A value used to compute a page of results (page number to replace %d = MoreStart + (MoreOffset x page)). If missing, the value 1 is used as the default.
Filter	String	A substring in an image URL that identifies the image as a search result. If missing, all images will be returned.
Ignore	String	A substring in an image URL that identifies the image as something other than a search result.
ImageSubs	Array	A list of operations for converting an thumbnail image URL to its associated source image URL. Each operation is specified with a pair of keys (see below) in a plist dictionary. Each operation is performed in the order they appear in the ImageSubs array.

Plist Key	Type	Description
Find	String	A string that is found in an image URL. Must be used with Replace, EraseTo or EraseFrom.
Replace	String	A string that replaces a found string in an image URL. Must be used with Find.
EraseTo	String	If present, identifies a EraseTo operation. Can be any string. Specific characters in an image URL (up to the Find string or up to the EraseToIndex) are erased. Must be used with Find or EraseToIndex.
EraseFrom	String	If present, identifies a EraseFrom operation. Can be any string. Specific characters in an image URL (following the Find string or from the EraseFromIndex) are erased. Must be used with Find or EraseFromIndex.
EraseToIndex	Number	The zero-based index from the start of the image URL. Must be used with EraseTo.
EraseFromIndex	Number	The zero-based index from the start of the image URL. Must be used with EraseFrom.
AddPrefix	String	If present, identifies a AddPrefix operation. Can be any string. Must be used with Prefix.
Prefix	String	A string that is added to the beginning of an image URL. Must be used with AddPrefix.
AddSuffix	String	If present, identifies a AddSuffix operation. Can be any string. Must be used with Suffix.
Suffix	String	A string that is added to the end of an image URL. Must be used with AddSuffix.